



COPY OF PAPER
ORIGINALLY FILED

8/19/02
#5

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Spurr

Serial No.: 09/784,466

Examiner: Joyce, William C.

Filed: 2/15/2001

Group Art Unit: 3682

Title: **Actuator Assemblies**

Commissioner of Patents
Washington, D.C. 20231

SUBMISSION OF PRIORITY DOCUMENT

Dear Sir:

Applicant is hereby submitting a certified copy of UK Patent Application number 0003686.3, dated February 18, 2000.

Favorable consideration if requested.

Respectfully submitted,

Anna M. Shih, Reg. No. 36,372
Carlson, Gaskey & Olds
400 W. Maple Road, Ste. 350
Birmingham, MI 48009
(248) 988-8360

Dated: 24 July 2002

CERTIFICATE OF MAIL

I hereby certify that the enclosed Response is being deposited with the United States Postal Service as First Class Mail, postage prepaid, in an envelope addressed to Assistant Commissioner of Patents, Washington D.C. 20231 on this 24 day of July, 2002.

Laura Combs



INVESTOR IN PEOPLE



The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

31 January 2001

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

The Patent Office

1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE
J
18 FEB 2000
NEWPORT

The Patent Office

Cardiff Road
Newport
Gwent NP10 8QQ

1. Your reference	JBJ/P240GB/44802000		
2. Patent application number (The Patent Office will fill in this part)	18 FEB 2000	18FEB00 E514223-2 001038 P01/7700 0.00-0003686.3	0003686.3
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Meritor Light Vehicle Systems (UK) Limited Fordhouse Lane Stirchley BIRMINGHAM B30 3BW UNITED KINGDOM Patents ADP number (if you know it) If the applicant is a corporate body, give the country/state of its incorporation UNITED KINGDOM		
4. Title of the invention	ACTUATOR ASSEMBLIES		
5. Name of your agent (if you have one) "Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	WITHERS & ROGERS Goldings House 2 Hays Lane London SE1 2HW Patents ADP number (if you know it) 1776001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number	Country /	Priority application number (if you know it) /	Date of filing (day / month / year) /
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application /	Date of filing (day / month / year) /	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES		

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form /
 Description 6
 Claim(s) 3
 Abstract 1
 Drawing (s) 2 + 2



10. If you are also filing any of the following, state how many against each item.

Priority documents /
 Translations of priority documents /
 Statement of inventorship and right to grant of a patent (Patents Form 7/77) /
 Request for preliminary examination and search (Patents Form 9/77) 1
 Request for substantive examination (Patents Form 10/77) /
 Any other documents (please specify) /

11. I/We request the grant of a patent on the basis of this application.

Signature Withers & Rogers Date 15 February 2000

12. Name and daytime telephone number of person to contact in the United Kingdom JONES John B - 0121 233 2997

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

JBJ/P240GB

Actuator Assemblies

The present invention relates to actuator assemblies and in particular actuator assemblies used to release or latch vehicle door latches.

Known actuator assemblies when used in vehicle door latches are only required to provide an output in one direction when actuating. The actuator assembly is returned to a rest position by powering of an actuator assembly motor in a reversed direction. This return stroke does no work.

Thus according to the present invention there is provided an actuator assembly including an actuator drivingly connected by a transmission path to an output member, the actuator being capable of moving the output member in a first direction from a rest condition of the actuator assembly to an actuated condition, and also being capable of moving the output member in a second direction from the actuated condition to the rest condition, the actuator assembly further including an energy storage means in which movement of the output member by the actuator in the first direction is assisted by the energy storage means, and movement of the output member in the second direction by the actuator stores energy in the energy storage means.

Advantageously such an arrangement allows the actuator assembly to produce a higher output force. Furthermore where the transmission path includes gears, smaller gears may be used. The invention also provides an actuator assembly which can operate faster. Furthermore the actuator assembly may produce the same output force with a lower powered actuator.

The invention will now be described, by way of example only, with reference to the accompanying drawings in which:-

Figure 1 is a view of an actuator assembly according to the present invention;

Figure 2 is a partial view of second embodiment of an actuator assembly according to the present invention:

Figure 3 is a view of a third embodiment of an actuator assembly according to the present invention; and

Figure 4 is a partial view taken in the direction of arrows C of figure 3.

With reference to Figure 1 there is shown an actuator assembly 10 including a housing 12 (only partially shown), an actuator in the form of an electric motor 14, a transmission path 16, an output member 18 and an energy storage means in the form of a compression spring 20.

The transmission path 16 includes a worm gear 22 which engages a worm wheel 24. Worm gear 22 is mounted rotationally fast on motor shaft 15.

Worm wheel 24 is rotationally mounted on the housing 12 and includes a crank pin 26.

Crank pin 26 engages in a lateral slot 28 of output member 18.

Output member 18 is guided by guides (not shown) for reciprocating linear movement in the direction of arrow A. Output member 18 has an output abutment 18A at one end thereof and a spring abutment 18B at the other end thereof.

Spring 20 is mounted between a portion 12A of housing 12 and spring abutment 18B of the output member 18.

Operation of the actuator assembly is as follows.

Figure 1 shows the actuator assembly in an at rest position with spring 20 having being compressed (see below). Thus spring 20 biases the output member 18 to the right as shown in Figure 1 and this bias load is resisted by the crank pin 26. In this case the helix angle of the teeth of the worm gear 22 and worm wheel 24, combined with the various frictional losses in the transmission path result in the bias load (spring force) provided by

compressed spring 20 being unable to back drive motor 14, i.e. turn motor 14. The actuator assembly thus remains in its at rest position shown in figure 1.

When actuation is required, an electrical current is supplied to motor 14 resulting in shaft 15 rotating and ultimately in worm wheel 24 rotating in an anticlockwise direction when viewing Figure 1. This results in the crank pin 26 moving from position B of Figure 1 to position C shown in Figure 1. This results in output abutment 18A contacting and moving further components (not shown) to, for example, release or latch an associated vehicle door latch. It will be noted that as output member 18 moves to the right as shown in Figure 1 it is assisted in moving in this direction by spring 20.

Once actuation has occurred, an electrical current is fed to the motor 14 causing it to run in a reverse direction resulting in the crank pin 26 moving from position C to position B and thus returning the output member to its at rest position. It should be noted that during the movement of the output member from its actuated position to its at rest position, spring 20 is caused to compress.

Thus when the actuator assembly is moving from its at rest position to its actuated position the spring 20 is releasing energy previously stored and acts to assist the motor. When the actuator assembly moves from its actuated position to its rest position the motor acts to compress spring 20, storing energy therein.

Once the reversing current to motor 14 has stopped, the actuator assembly remains in a position as shown in Figure 1 by virtue of the fact that spring 20 (which has now been compressed) is attempting to back drive motor 14 via the worm wheel and worm gear. Typically the worm wheel and worm gear would be 60% efficient and thus the various frictional losses associated with the sliding output member 18, the worm wheel and worm gear, and the motor are sufficient to ensure that the actuator assembly remains in the position as shown in Figure 1 even when no power is supplied to motor 14.

With reference to Figure 2 there is shown a second embodiment of an actuator assembly 40, identical to actuator assembly 10 apart from the fact that spring 42 has a higher spring rate than spring 20 and actuator assembly 40 also includes a detent arrangement 44 in the

form of a plunger 46 which is biased in the direction of arrow D by spring 48. Output member 50 includes a detent notch 52 into which plunger 46 can engage.

Thus when the actuator assembly 40 is in its at rest position as shown in Figure 2 plunger 46 engages detent notch 52 and acts to releasably retain the actuator assembly in its at rest position.

When the actuator assembly 40 is required to actuate, the motor is arranged such that it can, in conjunction with the increased load provided by spring 42, overcome the retaining action of the detent, following which the actuator assembly can produce a higher actuating output force as a result of the greater force provided by spring 42.

In this case the output member 50 is linearly moveable and the detent arrangement acts substantially normally to the direction of movement of the output member. In further embodiments the output member could move in a rotational direction and a detent arrangement could act substantially normally to this rotational direction i.e. radially inwardly or radially outwardly.

In an alternative embodiment a clutch arrangement could be used to ensure that the actuator assembly remains in its at rest condition.

Such an arrangement is shown in figure 3. In this case the motor is connected to worm wheel 60 rotatably mounted about axis A.

Worm wheel 60 includes a drive pin 62 secured thereto and also a stop pawl disengaging ramp 64 also secured thereto having a ramp surface 66 and a radially outer surface 67.

Also pivotally mounted about axis A is an output lever shown generally at arrow 68. Output lever includes and output pin 70, an arcuate slot 72, within which drive pin 62 sits, and assist spring abutment 74 and stop abutment 76. An assist spring 78 acts on assist spring abutment 74 and reacts against housing 12 (only part of which is shown).

Assist spring 78 biases the output lever 68 in a clockwise direction when viewing figure 3.

An output lever stop pawl 80 is pivotally mounted about axis B and is biased in an anticlockwise direction when viewing figure 3 by a spring 82 which reacts against housing 12. Pawl end 84 is provided for contact with stop abutment 76.

Operation of the actuator assembly is as follows:-

The actuator assembly is positioned as shown in figure 3 in its rest position. Thus the assist spring 78 has been compressed and the output lever 68 is prevented from being rotated in a clockwise direction under the influence of assist spring 78 by abutment of stop abutment 76 against pawl end 84.

Actuation of motor 14 causes worm wheel 22 to rotate such that worm wheel 60 is caused to rotate in a clockwise direction. Because of the arcuate slot 72, initially, drive pin 62 does not drive the output lever 68. However as the worm wheel rotates in a clockwise direction the ramp surface 66 of stop pawl disengagement ramp 64 acts on pawl end 84 to cam that end radially outward relative to axis A (it being noted from figure 4 that pawl end 84 is wide enough to be acted upon by both stop abutments 76 and stop pawl disengagement ramp 64). This causes pawl 80 to rotate in a clockwise direction until such time as the pawl end contacts the radially outer surface 67 of disengagement ramp 64. It should be noted that the radially outer surface 67 is positioned at a distance R from axis A which is greater than the outer most portion of stop abutment 76 (positioned at a radius r from axis A). Thus the stop pawl disengagement ramp 64 causes the stop pawl to disengage from the stop abutment 76 allowing the output lever 68 to rotate in a clockwise direction under the influence of assist spring 78 and drive pin 62 as it contacts end 72A of the arcuate slot 72.

This results in actuation of the components connected to output pin 70 since this pin moves from the position as shown in figure 3 clockwise for actuation.

Once actuation has been achieved, the motor 14 is powered in the reverse direction causing drive pin 62 to contact end 72B of the slot 72 which results in compression of the

assist spring 78 and ultimately re-engagement of pawl end 84 against stop abutment 76 once stop abutment 76 has being rotated past pawl end 84.

In this case since the output lever is positively retained in its at rest position by pawl 80, the load in assist spring 78 when the actuator is in its at rest position is limited only by the ability of the motor 14 to compress spring 78 to its at rest position, and not by the friction developed in the transmission parts from the output lever to the motor. It can be seen that the arrangement shown in figure 3 provides for a clutch arrangement for ensuring that the actuator remains in its at rest position.

In further embodiments clutch arrangements can be used on output members which act in a linear direction as opposed to a rotational direction.

It can be seen that the friction within a transmission path, the detent arrangement, and the clutch arrangement each act as a retaining arrangement which releasably retains the actuator assembly in its at rest condition against the influence of the energy storage device such a springs 20, 42 and 78.

Claims

1. An actuator assembly including an actuator drivingly connected by a transmission path to an output member, the actuator being capable of moving the output member in a first direction from a rest condition of the actuator assembly to an actuated condition, and also being capable of moving the output member in a second direction from the actuated condition to the rest condition, the actuator assembly further including an energy storing means, in which movement of the output member by the actuator in the first direction is assisted by the energy storing means and movement of the output member in the second direction by the actuator stores energy in the energy storing means.
2. An actuator assembly as defined in claim 1 in which the actuator is operably connected to the energy storing means by at least a portion of the transmission path.
3. An actuator assembly as defined in claim 1 or 2 in which the actuator assembly includes a retaining arrangement to releasably retain the actuator assembly in the rest condition.
4. An actuator assembly as defined in claim 3 in which the retaining arrangement is at least provided by friction associated with at least one of the actuator, the transmission path and the output member.
5. An actuator assembly as defined in claim 3 or 4 in which the retaining means is at least provided by a detent arrangement.
6. An actuator assembly arrangement as defined in claim 5 in which the detent arrangement acts upon the output member.
7. An actuator assembly arrangement as defined in claim 6 in which the detent arrangement acts substantially normally to the direction of movement of the output member.



8. An actuator assembly as defined in any one of claims 3 or 4 in which the retaining means is at least provided by a clutch arrangement.
9. An actuator assembly as defined in claim 8 in which the clutch arrangement includes a pawl acting on the output member.
10. An actuator assembly as defined in claim 9 in which the pawl is disengaged by a pawl disengagement ramp of a component of the transmission path.
11. An actuator assembly as defined in claim 10 in which said component of the transmission path has a lost motion connection with the output member.
12. An actuator assembly as defined in claim 10 or 11 in which said component of the transmission path is a worm wheel.
13. An actuator assembly as defined in any preceding claim in which the transmission path includes a worm gear and worm wheel.
14. An actuator assembly arrangement as defined in claim 13 in which the actuator is operably connected to the energy storage means by at least the worm gear and worm wheel.
15. An actuator assembly as defined in claim 3 or 4 in which the worm wheel includes a crank pin acting on the output member.
16. An actuator assembly as defined in any preceding claim in which the first and second directions of movement of the output member are linear directions.
17. An actuator assembly as defined in any one of claims 1 to 15 in which the first and second directions of movement of the output member are rotational directions.

18. An actuator assembly as defined in any preceding claim in which the energy storage means acts on the output member.
19. An actuator assembly as defined in any preceding claim in which the energy storage means is a resilient means.
20. An actuator assembly as defined in claim 19 in which the resilient means is a spring.
21. An actuator assembly as defined in claim 20 in which the spring is a compression spring.
22. An actuator assembly as defined in claim 20 in which the spring is a tension spring.
23. An actuator assembly as defined in any preceding claim including a housing which at least partially contains the actuator, transmission path and the output member.
24. An actuator assembly as defined in claim 23 when dependent upon claim 5 in which the housing at least partially contains the detent arrangement.
25. An actuator assembly as defined in claim 23 when dependent upon claim 8 in which the housing at least partially contains the clutch arrangement.
26. An actuator assembly as herein before described with reference to or as shown in figures 1 or 2 or 3 and 4 of the accompanying drawings.

Abstract

An actuator assembly (10) including an actuator (14) drivingly connected by a transmission path (16) to an output member (18), the actuator being capable of moving the output member in a first direction from a rest condition of the actuator assembly to an actuated condition, and also being capable of moving the output member in a second direction from the actuated condition to the rest condition, the actuator assembly further including an energy storing means (20), in which movement of the output member by the actuator in the first direction is assisted by the energy storing means and movement of the output member in the second direction by the actuator stores energy in the energy storing means (figure 1).

1/2



2/2.

